

SUPER #3000® MIX 22 MORTAR

Product Information Sheet

Monolithic Refractory

SUPER #3000® MIX 22 is a premium quality super duty grade mortar which has become an industry standard. This mortar has exceptional strength at low, intermediate and high temperatures. It is available in a variety of consistencies to meet individual application requirements. Excellent for all types of molten metal applications including aluminum and iron. Excellent mortar for boiler applications.

Service Temperature: 3000 °F **Material Required:** -
Typical Water Required: - **Maximum Grain Size:** -

Chemical Analysis

SiO ₂	Al ₂ O ₃	Na ₂ O + K ₂ O	Other				
44.5-49.5	44.6-49.6	3.05-3.55	2.35-2.85				

Typical Physical Properties

Tested in accordance with International and ASTM Standards

Prefired to	Bulk Density	Cold Crushing Strength	Cold Modulus of Rupture	Permanent Linear Change
(°F)	(lb/ft ³)	(psi)	(psi)	(%)

Other Physical Properties

Tested in accordance with International and ASTM Standards

Prefired to	Apparent Porosity	Thermal Conductivity	Hot Modulus of Rupture	Permanent Volume Change
(°F)	(%)	(Btu.in/h.ft ² .F)	(psi)	(%)

Formerly:

Product Number: LEY30369 MX3 MOR
 Effective Date: 12/11/2002

MSDS Reference: 1484
 Revision: A:00

The physical and/or chemical properties and specifications of the product set forth above represent typical average results obtained in accordance with generally accepted standard test methods conducted under controlled conditions, and are subject to normal manufacturing variations. Vesuvius reserves the right to modify the properties and specifications at any time without prior notice.



NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS INFORMATION, THE SUITABILITY OF THE PRODUCT FOR A PARTICULAR PURPOSE, OR THE RESULTS TO BE OBTAINED BY THE USE OF THE PRODUCT. USERS EXPRESSLY ASSUME ALL RISKS AND LIABILITIES ARISING FROM THE USE OF OR RELIANCE UPON THIS INFORMATION.